



Specification Note:

The following specifications call out the material and default installation requirements necessary for the floor as recommended by Robbins Performing Arts. In some cases, local codes, physical requirements or installer recommendation may override these methods and procedures. It is Robbins Performing Arts recommendation to review the specification with a Regional Sales Manager or the local Authorized Dealer before incorporating the specification into the project design. Some options impact installed cost and verification of the design and budget is advised.

For the name of the local Robbins Performing Arts representative or dealer, call 1-800-831-8987.

SECTION 09 / GUIDE SPECIFICATIONS FOR
ROBBINS® PERFORMING ARTS ÉLAN BASKETWEAVE VINYL FLOOR SYSTEM

SECTION 09 64 00 – WOOD DANCE FLOORING

PART 1 GENERAL

1.1 SUMMARY

- A. Provisions of Division 01 may apply to this section
- B. SECTION INCLUDES
 - 1. A sprung dance floor system with a vinyl surface.
- C. RELATED SECTIONS (A cross-reference should be incorporated in these sections.)
 - 1. Section 03 30 00: Cast-in-Place Concrete.
 - a. Concrete and Slab Construction: refer to ACI Code 302.1R-04.
 - b. Concrete Slab Depression: 3 11/16" (94mm).
 - c. Surface Finish: steel troweled and finished smooth.
 - d. Concrete Tolerance: +/- 1/8" (3mm) in radius of 10' (3m).
 - e. Floor Flatness and Floor Levelness (FF and FL) numbers are not recognized.
 - f. High spots shall be ground level and low spots shall be filled in with approved leveling compound by the general contractor to meet the tolerance above.
 - g. Compressive Strength: Concrete shall be a minimum of 3,000 psi (21 MPa) and a maximum of 4000 psi (28MPa) compressive strength after 28 days. Concrete shall be free of washed river gravel, pea gravel, flint or hardener additives. No lightweight concrete.
 - 2. Section 07 10 00: Dampproofing and Waterproofing.
 - a. Concrete subfloors on or below grade shall be adequately waterproofed beneath the slab and at the perimeter walls and on the earth side of below grade walls by general contractor using suitable type membrane.
 - b. Sand-Poly-Sand slab construction is not an acceptable construction.
 - 3. Section 08 70 00: Door Hardware – Thresholds.
 - 4. Section 09 90 00: Paints and Coatings
 - 5. Section 11 60 00: Entertainment Equipment.

1.2 REFERENCES

- A. ANSI E1.26 -2006 (R2012): Entertainment Technology - Recommended Testing Methods and Values for Shock Absorption of Floors Used in Live Performance Venues
- B. FSC: Forest Stewardship Council®

1.3 SUBMITTALS

- A. Submit under provisions of Section 01 30 00: Administrative Requirements.
- B. Specification: Robbins Performing Arts **Élan Basketweave Vinyl** specification sheet.
- C. Drawings: Submit Robbins Performing Arts **Élan Basketweave Vinyl** drawing.
- D. Material Sample: Submit one (1) sample of Robbins Performing Arts **Élan Basketweave Vinyl**, if requested by architect.
- E. Maintenance Guidelines: Submit copy of Maintenance Instructions.
- F. Submit Robbins Technical Services “Concrete Guide Specification” for further information regarding conditions and requirements of concrete prior to installation.
- G. Installer and Manufacturer Qualifications: Documentation showing compliance with manufacturer and installer qualifications specified in the Quality Assurance paragraph.

1.4 QUALITY ASSURANCE

- A. Floor System Manufacturers Qualifications
 - 1. Basis of design shall be **Élan Basketweave Vinyl** floor system as provided by Robbins Performing Arts, www.robbynsdancefloors.com, (800-831-8987).
 - 2. Manufacturer shall be an established firm experienced in field and have been in business for a minimum of ten (10) years; Robbins, Inc. or an approved equal.
 - 3. Material other than those listed must be approved 10 days prior by written addendum. Materials from un-approved manufacturers will not be accepted.
- B. Floor Contractor/Installer Qualifications and Certifications
 - 1. The flooring contractor shall be a Robbins Accredited Installer and be on site for the duration of the floor installation; or, a contractor approved by Robbins Performing Arts.
 - 2. Flooring contractor shall be an established firm experienced in field and have been in business or a minimum of ten (10) years; Robbins, Inc. or an approved equal.
 - 3. Flooring contractor shall submit a list of at least three completed projects of similar magnitude and complexity completed under current corporate identity.
 - 4. Flooring contractor shall be manufacturer trained.
- C. Floor System Design
 - 1. Flooring system shall have dual pad design for vibration damping and resiliency.
 - 2. Optional anchorage for dimensional stability over time.
 - 3. Resilient pad shall be made from 50 durometer EPDM rubber.
 - 4. Resilient pad shall have built in stop blocks
- D. Floor System Performance
 - 1. **Élan Basketweave Vinyl** shall be tested to the following performance criteria:
 - a. ANSI E1.26 -2006 (R2012)

1.5 DELIVERY, STORAGE, AND HANDLING

- A. Materials shall not be delivered, stored or installed until all masonry, painting, plastering, tile, marble and terrazzo work is complete, and all overhead mechanical work, lighting, other overhead units are installed. Room temperature of 65-80 degrees Fahrenheit (18 to 27 degrees Celsius) and relative humidity of 35-50 % are to be maintained. The building shall be enclosed and weather tight. Ideal installation/storage conditions are the same as those that will prevail when building is occupied
- B. Materials shall not be delivered, stored or installed at the installation location if the In-Slab relative humidity level for the concrete slab is above 85% using ASTM F 2170 In-Slab Relative Humidity test.

1.6 PROJECT CONDITIONS-SEQUENCY

- A. Do not install floor system until concrete has been cured 60 days and the requirements in Article 1.5 are obtained.
- B. General Contractor is responsible to ensure slab is clean and free of all dirt and debris prior to floor installation beginning.
- C. Maintain room temperature at 65 to 80 degrees F (18 to 27 degrees C) for one week prior to delivery of materials, during installation, and after installation.
- D. Provide permanent electricity, heat, light, and ventilation 1 week prior to delivery of materials, during installation, and after installation. Maintain a temperature range of 65 to 80 degrees Fahrenheit (18 to 27 degrees Celsius) and a relative humidity range of 35 to 50%.
- E. Acclimatize wood flooring in accordance with period of time recommended by manufacturer. In applications in which very high or low levels of humidity are present, extend period of time accordingly.

1.7 WARRANTY

- A. Guarantee shall not cover damage caused in whole or in part by casualty, ordinary wear and tear, abuse, use for which material is not designed, faulty construction of the building, settlement of the building walls, failure of the other contractors to adhere to specifications, separation of the concrete slab and excessive dryness or excessive moisture from humidity, spillage, migration through the slab or wall, or any other source.
- B. Robbins Performing Arts hereby warrants the **Élan Basketweave Vinyl** material to be free from manufacturing defects for a period of 2 years and the integrated vinyl surface for 5 years. This warranty is in lieu of all other warranties, expressed or implied including but not limited to any warranty of merchantability or fitness for a particular purpose, and of any other obligations on the part of Robbins Performing Arts. In the event of breach of any warranty, the liability of Robbins Performing Arts shall be limited to repairing or replacing **Élan Basketweave Vinyl** material and system components supplied by Robbins Performing Arts and proven to be defective in manufacture, and shall not include any other damages, either direct or consequential.

PART 2 PRODUCTS

2.1 MANUFACTURERS

- A. Acceptable Manufacturer: Robbins Performing Arts, which is located at: 4777 Eastern Ave; Cincinnati, OH 45226; Toll Free Tel: 800-831-8987; Fax: 513-871-7998; Email: [request info \(info@robbinsdancefloors.com\)](mailto:info@robbinsdancefloors.com); Web: www.robbinsdancefloors.com
- B. Substitutions: Not permitted.
- C. Requests for substitutions may be considered in accordance with provisions of Section 01

60 00 - Product Requirements.

2.2 MATERIALS

- A. Vapor Barrier
 - 1. 6-mil polyethylene.
- B. Subfloor
 - 1. 7/16" thick 50 durometer pads.
 - 2. 7/16" Open cell force attenuation resilient pad strip.
 - 3. 3 layers of Élan Basketweave Battens
 - 4. Subfloor layer of Exposure 1, APA Rated sheathing
 - 5. Upper layer of Exposure 1, APA Rated sheathing
 - 6.
- C. Surface
 - 1. Robbins Dance Vinyl
- D. Fasteners
 - 1. Subfloor Fasteners: 1 ¼ (32mm)" coated staples or equivalent.
 - 2. Subfloor Fasteners: 1 (25mm)" coated staples or equivalent.
 - 3. Adhesive: Elastomeric subfloor adhesive.
 - 4. Optional Sleeper Anchors: Powers SPIKE® anchors and sleeves
- E. Perimeter Base
 - 1. 3" x 4" heavy duty ventilating type base with pre-molded outside corners.(Specify black or brown)

PART 3 EXECUTION

3.1 INSPECTION

- A. Inspect concrete slab for proper tolerance and dryness, and report any discrepancies to the general contractor and architect in writing. Slab will be level to within 1/8" (3mm) in a 10' (3m). Moisture content of the concrete slab not exceed 85% in accordance to ASTM F 2170 In-Slab Relative Humidity test.
- B. All work required to put the concrete subfloors in acceptable condition shall be the responsibility of the general contractor.
- C. Floor area shall be broom cleaned by general contractor.
- D. Verify that site conditions are acceptable for installation of wood flooring system.
- E. If substrate preparation is the responsibility of another installer, notify Architect of unsatisfactory preparation before proceeding. Do not begin installation until substrates have been properly prepared.
- F. Installer shall document all working conditions provided in General Specifications prior to commencement of installation.

3.2 INSTALLATION

- A. Vapor Barrier
 - 1. Install polyethylene with joints lapped a minimum of 6" (150mm) and turned up at walls 4"(100mm).
- B. Subfloor
 - 1. Install Robbins resilient and force attenuation pads on sleepers per manufacturer's

recommendations.

1. Install padded Élan Basketweave battens end to end at right angles to finished flooring. Sleepers shall be staggered with rows spaced 16" (406mm) on center. Allow for a ¼" (6mm) gap between batten ends. Provide 1-½" to 2" (40 to 50mm) expansion void at the perimeter and all vertical obstructions.
2. Install secondary Élan Basketweave battens end to end at right angles to the first layer of Battens per manufacturer's instructions. Sleepers shall be staggered with rows spaced 16" (406mm) on center. Allow for a ¼" (6mm) gap between batten ends. Provide 1-½" to 2" (40 to 50mm) expansion void at the perimeter and all vertical obstructions.
3. Install third layer of Élan Basketweave battens end to end at right angles to the second layer of Battens per manufacturer's instructions. Sleepers shall be staggered with rows spaced 16" (406mm) on center. Allow for a ¼" (6mm) gap between batten ends. Provide 1-½" to 2" (40 to 50mm) expansion void at the perimeter and all vertical obstructions.
4. If chosen, anchor Élan Basketweave sleepers using per manufacturer's instructions. Maintain a 2" (50mm) minimum expansion void at all walls and other permanent vertical obstructions.
5. Install solid blocking at doorways and other transition areas.
6. Install partial blocking per manufacturer's recommendations.
7. Install APA rated sheathing parallel the Élan Basketweave battens, staggering panels in adjacent rows. Fasten subfloor sheathing to sleepers using 1-¼" (35mm) staples placed 6" (150mm) on center along each sleeper.
8. Install the upper plywood subfloor perpendicular to the lower subfloor panels staggering joints and spacing 1/8" (3mm) apart. Secure these panels using adhesive and staples per manufacturer's instructions.
9. Fill and sand seams pre manufacturer's instructions for smooth surface for vinyl surface.

C. Flooring Surface

1. Install Dance Vinyl per manufacturer's instructions.

3.3 INSTALLATION OF WALL BASE

- A. Install vent cove base anchored to walls with base cement or mechanical fastener. Use pre-molded outside corners and neatly mitered inside corner.

3.4 CLEANING AND PROTECTION

- A. Remove rubbish, debris, and waste material from work area and legally dispose.
- B. After floors are finished, area to be kept locked by general contractor to allow curing time for the finish. If after required curing time general contractor or owner requires use of the floor, he shall protect the floor by covering with non-fibered kraft paper or red rosin paper with taped joints, until acceptance by owner (or owner's agent) of complete dance floor. Take necessary precautions to prevent damage from dropped objects. Use breathable materials to cover installed wood flooring. Do not completely cover installed wood flooring, as moisture and color shading issues may arise.
- C. Clean floor surface using cleaning products recommended by flooring manufacturer.

3.5 INSTRUCTION

- A. Instruct Owner's designated representatives in flooring maintenance.

END OF SECTION

Construction options are available to modify this system to the project design and budget.

Contact your Regional Sales Manager(1-800-831-8987) or the local Authorized Dealer for more information.