



AKTIVPLUS PRODUCT SPECIFICATION

Dimensions: 1/2" x 48" wide rolls

FORCE REDUCTION	ASTM F2772	19.70%
ENERGY RESTITUTION	ASTM F2772	80.20%
ABRASION RESISTANCE	ASTM D3389	<1.7g, 1000 cycles
STATIC LOAD LIMIT	ASTM F970	0.001" @ 250 PSI
COEFFICIENT OF FRICTION	ASTM D2047	>0.95
SLIP RESISTANCE	ASTM F2772	Pass
PILL TEST	ASTM D2859	Pass
VOC COMPLIANT	ASTM D5116	Yes
DENSITY	ASTM D3676	60 pcf
HARDNESS	ASTM D2240 (Shore A)	60 +/- 5
TEAR STRENGTH	ASTM D624	80 pli min
ELONGATION	ASTM D412	>145%
TENSILE STRENGTH	ASTM D412	>220 PSI
FLEXIBILITY	ASTM F137 1/4" Mandrel	Pass
RESISTANCE TO CHEMICALS	ASTM F925	No Change
LEED QUALIFICATION	Qualifies for Material and Resources Credit	
ROLLING LOAD	EN1569	Pass
IMPACT	EN1517	14 N/m
INDENTATION	EN1516	0.1mm
VERTICAL DEFORMATION	ASTM F2772	1.4mm

