

U.S. Patent# 7,694,408



Robbins' Premier Performing Arts Flooring System



FLOOR TYPE: Sprung Floor: Anchored

FLOOR SURFACE: Northern Hard Maple Flooring

FLOOR SYSTEM THICKNESS: 2¹⁵/16" (75mm) Note: System can be easily modified to achieve a different height

APPLICATIONS: Ballet, Contemporary, Modern, Classical, Ballroom, Hip Hop, Swing, Jazz, Theatrical, Multi-purpose


FLOOR BUILD-UP

- 1. Hardwood floor polyurethane finish.
- 2. Hardwood floor polyurethane seal.
- 3. 25/32" x 1 ¹/₂"specially profiled hardwood maple flooring.
- 4. Semi-flexible load distribution sheathing layer.
- 5. Laminated Danzaire Panel with thick resilient pad
- 6. Anchoring Pin and Metal Retainer.
- 7. 6 mil Polyethylene vapor retarder.

FEATURES

- Durable Performance Surface: solid hardwood surface that is recoatable and refinishable.
- Load distribution deflection plate: Delivers vitally important foot stability.
- Patented Sprung Subfloor Design: A Proprietary design with Specially formulated cushion layer that provides outstanding Uniformity of performance.
 - Balanced Shock Absorption & Energy Return for Enhanced performance and longevity.
 - Vibration Tuning and Damping Controls acoustic and sensory vibration.
 - Anchor Pattern facilitates uniformity of all performance characteristics.

*FSC® Materials Available for Purchase



DANZAIRE has been tested per the ANSI E1.26 Standard



Performance like NO other... For Dancers, By Dancers

Robbins most advanced professional sprung floor systems are designed & biomechancially researched, specifically for performers with dancer input to create the world's most comfortable and highest performing surfaces. Robbins unique dance floor designs clearly unites legendary performance with all the qualities necessary to withstand the rigors of even the most demanding venues, delivering long-lasting, superior performance characteristics that traditional sprung floors cannot. Outstanding uniformity, vibration control, impact force reduction, and deflection allow performers of all levels to concentrate on their art, **not** the fear of falling or potential injury.

Characteristics of a Superior Dance Floor System* Includes:

- Significant enhancements to dancer "comfort".
- Provides unparalleled uniformity in feel and performance
- Tightly controls magnitude and timing of deformation for proper energy return
- Damps vibration, quickly limiting effect on neighboring performers
- **Minimizes** floor system vibration in general and specifically in the natural frequency range of soft tissue packages, providing comfort and reducing fatigue
- **Separates** the input vibration frequency (i.e., the skeletal deceleration (frequency) from the natural frequency of soft tissue packages
- Induces small Electromyography (EMG) muscle activity response
- Limits the amount of flooring set into motion upon impact through excellent deformation control
- Provides outstanding acoustics control of audible vibration
- Eliminates excessive rebound e.g., "trampoline effect"
- Prevents "hard & soft spots" through uniform suspension across the entire floor
- Uniformity, vibration control, and force reduction working together in unison to dramatically enhance performance, while also increasing comfort and safety.
- Provides excellent stability under theatrical loading. *defined by Dr. Benno Nigg, The Human Performance Lab, University of Calgary



Recent DanzAire Installations:

EDGE Performing Arts Center (Los Angeles, CA) Reed College (Portland, OR) Kentucky Center for the Arts (Louisville, KY) The Banff Centre (Banff, Alberta, CA) Choate Rosemary Hall (Wallingford, CT) Tracey Anderson Manhattan Studio (New York, NY) Carleton College (Northfield, MN) Buckley School (New York, NY)

