

Premium Rubber Flooring





Smooth rubber surface with natural coconut husk fibers.



THICKNESS

6 ft 2 in x 32 ft 9 in

(1.9 m x 10 m)

0.118 in



WEIGHT





TILES 24 in x 24 in (61 cm x 61 cm)



MONDO's unique Dual Durometer Technology is a process through which a wear layer is molecularly bound to a bottom performance layer. It increases the durability and performance

DURABILITY

UV cured MONDOshield maintenance mitigation system Proven wear abrasion resistance - ASTM D3389 High stain and chemical resistance - ASTM F925 Great static and rolling load resistance 15-year wear warranty

COMFORT

Noise absorption qualities for improved acoustics - ISO 10140-3 Impact Sound Trasmission Reduction - ASTM E2179 Increased underfoot comfort with anti-fatigue properties Superior product resiliency

LIFE-CYCLE COST/EASE OF MAINTENANCE

Low overall cost of ownership from savings on maintenance Demonstrated long life expectancy No waxing required

SAFETY

Excellent fungal, bacterial and microbial resistance throughout Slip resistance - complies with ADA 302 Floor and ground surfaces

Class 1 fire rated - ASTM E648 Resisntace tu Fungi - ASTM G21

ENVIRONMENTAL STEWARDSHIP

EPD and HPD 100% recyclable Does not contain any LBC red listed ingredient GREENGUARD Gold certified Meets CA section 01350

10% pre-consumer recycled content 4% rapidly renewable content

Cradle to Cradle Certified® Silver

Specs



















WITH DUAL DUROMETER TECHNOLOGY

of the flooring and allows for a long-lasting appearance.



K104 Lacey Pearl

K073 Clean Canvas

K052 Natural Light

K049 Ozone















K058 Soft Toffee


K038 Thyme





















Sustainability Credential









