

RAMFLEX

WEIGHT AND SKATE
RESISTANT RUBBER FLOORING



RAMFLEX

Versatile rubber flooring engineered for weight and skate resistance and the staple surface for fitness.

RAMFLEX



SPECIFICATIONS

Texture: Hammered
 Thickness: 15/64" (6 mm)
 Roll Width: 6' 1" (1.86 m)
 Roll Length: 42' 7" (13 m)*

Thickness: 25/64" (10 mm)
 Roll Width: 6' 1" (1.86 m)
 Roll Length: 29' 6" (9 m)*

Tile Dimensions: 3' x 3'
 (0.91 m x 0.91 m)

COLORS**



Dark Maple G920



Red G741



Brown G715



Beige G712



Grey G707



Blue G710



Marine Blue G986



Solid Black G790

VULCANIZED ADVANTAGE

Mondo's vulcanization process permanently amalgamates individual layers, using high heat and pressure; the product will never separate, and its biomechanical and physical properties will be consistent. Each vulcanized layer offers individual characteristics and benefits.

PERFORMANCE LAYER

- 2 mm homogeneous wear layer for high performance with ice skate traffic as well as strength and conditioning equipment
- Straightforward maintenance, requires no finishes or coatings

IMPACT LAYER

- Protects against impact and high intensity training
- Glued down installation eliminates bacteria or mold growth

KEY BENEFITS

- 20+ years life expectancy
- Low cost of ownership

- Provides shock absorption and dimensional stability
- Withstands static loads such as weights and cardio equipment

HEALTH AND SAFETY

- GREENGUARD Gold certified, the most stringent indoor air quality requirement testing
- 100% recyclable; contains pre-consumer, post-consumer recycled content and rapidly renewable material
- Fire resistant
- Meets ADA requirements

- Free of halogens, isocyanates, formaldehyde, asbestos, bisphenol (BPA), halogenated flame retardant-free, heavy metals, phthalates, polychlorinated biphenyls (PCBS), perfluorinated compounds (PFCS)
- Excellent fungal, bacterial and microbial resistance throughout



Printed in Canada - Revised 02/2020

*Average length from production.

**Custom colors available; minimum quantity required.

The degree and type of marbleization will vary.