

ECLIPSE® SB



PERFORMANCE, DURABILITY, AFFORDABILITY... PLUS SUPERIOR HIGH LOADING CAPABILITY







- Safeguard the well-being of the athlete
- O Ensure good game play performance
- Provide good structural integrity

Robbins pioneered the use of DIN in North America more than 20 years ago and continues to be the industry leader with more than 25 patents and numerous floor system innovations in use every day. Robbins latest design, *Eclipse SB*, was built to be a COMPETITION CLASS FLOOR that delivers outstanding biomechanic response and game play performance. It withstands the rigors of every-day use, while also handling heavy rolling loads such as bleachers, portable basketball goals, and heavy equipment. And to top it off, we also designed it to be AFFORDABLE. Only Robbins could pack this much performance into a single system!



So whether you're in charge of an elite NBA, NCAA or high school program, or just looking for the best value for your money at any level of play, you owe it to yourself to take a look at what *Eclipse SB* has to offer.

robbinsfloor.com | 1.800.543.1913

ECLIPSE® SB

(FLOATING)



Product Specifications

System Type Floating Panel
 Slab Depression 2"(51 mm) with 25/32" (20 mm) Maple

Surface- MFMA Robbins Continuous Strip® XL (FJ)
Northern Hard Maple

Exceeds Industry
Standards for both
Anchored & Floating:

PUR COMPLIANT

MFMA PUR
DIN 18032 part 2 2001
DIN 18032 part 2 1991
ASTM F2772-09
FIBA Level 1
EN 14904 Type 4

O LEED Contributions



MR credit 4, 5, & 7
IEQ 4.1, 4.2, 4.3, 4.4
FSC[©] Lumber Available
*Credits are based on products selected and location of facility

Subfloor Construction Double layer Plywood Nominal 1" Subfloor

Resilience Layer


Bio-Sport II Pad

Optional Construction

Contact a Robbins Representative for Alternative Systems

Warranty
Egis


1 year Industry Standard with optional Extended Warranty Program (*Egis Floorlife*) Wall View



Threshold View

1/4" (6mm)|Threshold Plate
1.5" - 2" (38mm - Stmm) Expansion Void
Solid Stop Block
7/16" (11mm) Resilient Pad
Eclipse \$6 Subfloor Panel
27/22" (20mm) MFMA
Maple Flooring
6 MIL Vapor Barrier
22" (51mm)
Concrete Slab

Equipment View



Eclipse Family Reference Facilities

South Bend Charter School, South Bend, IN - 8,145 SF

Regis Sacred Heart Houston, TX - 7,665 *SF*

Bishop Chatard High School Indianapolis, IN - 10,002 SF

*All reference facilities are anchored systems



robbinsfloor.com | 1.800.543.1913