## Robbins 👯 Sportwood® Ultra Star

## A sports floor good for the Environment & the Athlete



Robbins

You expect a lot from your athletic floor. DURABILITY. ATTRACTIVENESS. COMFORT and SAFETY. And you know better than to think that, when it comes to floor coverings, "one size fits all." So does Robbins. That's why Sportwood Ultra Star is the perfect floor for you - no matter what you require.

Sportwood Ultra Star is solidly constructed of beautiful MFMA PQ edge-grain northern hard maple and features an adaptable, "tunable" underlayment.

Elastomeric urethane adhesive bonds the maple Sportwood to layers of stabilizing load-distribution subfloor, sitting atop a matrix of our EPDM rubber Bio-Pads or alternate resilient element. These pads can be adjusted, or "tuned," to your desired level of shock absorption - making Sportwood Ultra Star ideal for any number of activities. Whether you need shock absorption security for aerobic, basketball or other sports, or simply want a comfortable multi-use surface for cafetoriums or other facilities, simply specify the amount of resiliency needed, and Robbins will take care of the rest. The load- distibution subfloor, plus the resilient shock-pads, allows Sportwood Ultra-Star floors more "give" - meaning less chance of foot, leg or back injury. In addition to this safety feature, Sportwood Ultra Star is the most dimensionally stable maple product on the market, able to withstand even extreme moisture conditions.

- The traditional appearance of Sportwood is constructed with genuine, edge-grain cut, Northern Hardwood Maple, a long preferred surface in many basketball, volleyball and other indoor sport facilities
- Sportwood is an environmentally friendly product that is comprised of off-fall hardwood materials

ROVEN	PROVEN	PROVE
afety	Performance	Winne

## Robbins 🛝 Sportwood® Ultra Star



## **Product Specifications**

		•	
O System Type	Floating Parquet Panel	Wall View 7/16° (11mm) Resilient Pad 1.5°- 2° (38mm-51mm) Expansion Void 3° (76mm) x 4° (102mm) Vented Cove Base	
<b>O</b> Slab Depression	1 ¾" (44mm) with 7/16" (11mm) maple and 7/16" (11mm) pad 2" (51mm) with 7/16" (11mm) maple and ¾" (19mm) pad	Concrete Slab	
Surface- MFMA Northern Hard Maple	7/16" (11mm) thick maple parquet flooring	Solid Stop Block	
Environmental Impact	Sportwood is an environmentally friendly product comprised of off-fall hardwood materials	Concrete Slab	
Subfloor Construction	2 layers of nominal ½" or 7/16" x 48" x 96" (12mm x 1219mm x 2438mm) exposure 1,rated subfloor sheathing	Insert Plate 1.5"- 2" (38mm-51mm) Expansion Void 7/16" (11mm) MEMA Maple Flooring 6 ML Vapor Barrier 1 3/4" (44mm)	
<b>O</b> Resilience Layer	Many pad options available	Concrete Slab	
<b>O</b> Vapor Barrier	6 MIL Polyethylene	<u>Sportwood Ultra Star</u> <u>Reference Facilities</u>	
Optional Construction	Contact a Robbins Representative for Alternative Systems	Auburn University Airdrie Recreation Centre University of Alaska LSU Recreation Center Wichita State University Simon Fraser University Olivet College East Kentwood High School Palo Alto High School Milford High School Texas A&M University YMCA (multiple locations)	
O LEED Contributions	MR credit 4, 5, & 7 IEQ 4.1, 4.2, 4.3, 4.4 FSC <sup>©</sup> Lumber Available *Credits are based on products selected and location of facility		
Warranty Egis	1 year Industry Standard with optional Extended Warranty Program ( <i>Egis Floorlife</i> )		
	rabbingfloor com 1 1800 EA		

robbinsfloor.com

1.800.543.1913