

COLOR INFUSED



*Color Infused*  
**MODULAR ACOUSTIC FLOORING**



TAJ-6533C Batten-Daybreak



TAJ-6541X Board-Ice



TAJ-6557C Balance-Coal  
TAJ-6537C Batten-Coal



TAJ-6531C Batten-Ice  
TAJ-6537C Batten-Coal





TAJ-6551C Balance-Ice



TAJ-6540X Board-Buff



TAJ-6557C Balance-Coal



TAJ-6545X Board-Lodge



HOT COCOA  
&  
COFFEE  
BAR  
*Love is Brewing*

WINE A BIT  
IS  
BETTER  
ALWAYS  
FOR A GLASS  
WINE

Save  
Water  
WINE  
ONES  
FRIENDS  
DRINK  
SOMEONE

WINE  
LIFE  
TOO SHORT  
DRINK

**BOARD**

**BATTEN**

**BALANCE**

**BOARD**

**BATTEN**

**BALANCE**

**LEAF**



TAJ-6542X



TAJ-6532C



TAJ-6552C

**BUFF**



TAJ-6540X



TAJ-6530C



TAJ-6550C

**ICE**



TAJ-6541X



TAJ-6531C



TAJ-6551C

**TRUFFLE**



TAJ-6546X



TAJ-6536C



TAJ-6556C

**DAYBREAK**



TAJ-6543X



TAJ-6533C



TAJ-6553C

**COAL**



TAJ-6547X



TAJ-6537C



TAJ-6557C

**CURRY**



TAJ-6544X



TAJ-6534C



TAJ-6554C

**LODGE**



TAJ-6545X



TAJ-6535C



TAJ-6555C

*Additional Batten colors can be found in the Spectrum Collection*

*Visit [tajflooring.com](http://tajflooring.com) for more images of all colors*



# Color Infused

## Technical Specification Information

TAJ Color Infused is a high performance 5mm fiberglass reinforced modular acoustic flooring product with a non-slip backing. This advanced modular construction allows for multiple installation options in varied commercial end use applications. TAJ Color Infused is appropriate for use over raised access floor panels, excellent for limiting sound transmission, and installs nicely next to carpet tile without the need for transition strips.

**Classification:** ASTM F1700 Class III  
Type B (embossed)

**Overall Thickness:** 5.0mm

**Dimensions:**  
Plank 7.25"x 48.5" nominal (7.36"x 48.46" actual)  
Slab 12"x24" nominal (11.97" x 23.9" actual)

**Wear Layer Thickness:** .5mm, 20mil

**Wear Layer:** High Molecular Weight Polymerized Vinyl

**Finish:** Protech Plus (Ceramic Bead Infused UV Cured Polyurethane with anti-microbial technology)

**Edge Detail:** Square Edge (no bevel)

**Warranty:** 15 year Commercial Warranty

**Maintenance:** Requires no wax, no stripping, no buffing or the use of toxic chemicals

**Static Load Limit:** ASTM F970 modified, passes at 1,000 psi, residual compression maximum 0.005"

**Chemical and Stain Resistance:** ASTM F925, Excellent  
No surface dulling, surface attack, or color change with 5% acetic Acid, 70% isopropyl alcohol, mineral spirits, 5% sodium hydroxide, 5% hydrochloric acid, 5% ammonia, bleach, 5% phenol, gasoline, sulfuric acid, kerosene, and olive oil.

**Slip Resistance:** ASTM C1028-89, >0.6

**Flame Spread:** ASTM E648, >.45, Class 1

**Smoke Density:** ASTM E662, <450

**Low Emitting Flooring:** LEED IEQ4.3

**Low Emitting Adhesives:** LEED IEQ4.1

**Recycled Content:** 100% Phthalate Free Virgin Materials

**Impact Sound Conduction:** ASTM E492, IIC 57

**Airborne Sound Transmission Loss:** ASTM E90, STC 62

**Indoor Air Quality:** CHPS 1350 Certified

**Indoor Air Quality:** FloorScore Certified

**Plant Certifications:** ISO14001, ISO9001



Revit files available for  
download at [tajflooring.com](http://tajflooring.com).

\*For details on Health and Environmental Product Declarations, recycled content please email request to [info@tajflooring.com](mailto:info@tajflooring.com)

Visit us at [tajflooring.com](http://tajflooring.com) for complete specifications and to order samples.



740 Church Road, Elgin, IL 60123  
(888) 652-2111 | [tajflooring.com](http://tajflooring.com)